

Dell™ PowerConnect™ 6200 Series Switches



The PowerConnect™ 6200 series is Dell's most advanced switching product line, offering advanced switching capabilities including high density, high performance stacking and 10 Gigabit Ethernet' capabilities scalable from the small business to the Enterprise Edge.

High Density

The PowerConnect 6200 series will offer versions with 24 and 48 ports of 10/100/1000 BASE-T Gigabit Ethernet'. Delivering significant rack density, the PowerConnect 6200 gives users the flexibility to maximize server and workstation connectivity in a 1U form factor. Up to 576 servers and/or clients can be connected in a stack of 6200 series switches to help provide the maximum density, flexibility and manageability.

High Performance Stacking

The PowerConnect 6200 series supports high performance resilient stacking up to twelve systems, which allows increased throughput to be added as needed without affecting network performance. With each switch supporting up to 232Gbps in switch capacity, the customer can have almost 3 Terabytes of capacity in a single stack!

10 Gigabit Ethernet'

The PowerConnect 6200 series switches support up to four 10 Gigabit Ethernet' uplinks for connectivity directly to 10GE routers, enterprise backbones and data centers.

Advanced Layer 3 Capabilities

The PowerConnect 6200 series supports advanced Layer 3 routing and multicast protocols to help reduce congestion and manage traffic in the network. The PowerConnect 6200 series supports frequently used LAN routing protocols such as RIPv1/v2, OSPFv2/v3, VRRP, IGMP, DVMRP and PIM.

Advanced QoS

The PowerConnect 6200 offers flexibility in Quality of Service (QoS) by giving network administrators the ability to prioritize time-critical network traffic based on a variety of user-defined criteria. Administrators can expedite traffic based on L2 or L3 information, such as IP ToS, and provide greater control over traffic flow within the network.

Advanced Security

Support for up to 1024 L2-L4 Access Control Lists (ACLs) on the switch allows the user to perform deep packet inspection. 802.1x port authentication offers both single and multiple host access. Further security is provided through Denial of Service (DoS) Attack Prevention, whereby the switch can protect against common network attacks, such as Blat, Land, Smurf, Ping of Death, Xmascan, Nullscan, Scan SYNFIN, in addition to CPU attacks, such as VLAN flooding, TCP SIM, TCP port scan, IP address Spoofing and MAC address spoofing.

IPv6 Ready

IPv6 is version six of the "Internet Protocol" that has been in development for over 20 years. IPv6 has been designed to address IP address limitations of previous version of the Internet Protocol, enabling an increased number of unique IP addresses for broader scalability worldwide now and in the future.

Value and Flexibility

The PowerConnect 6200 series offers additional value because the unique modular design allows you to upgrade to advanced stacking or 10 Gigabit Ethernet' only when you need it. Plus we offer further flexibility and value with the optional modules that allow for either 10 Gigabit optical or CX-4 copper interfaces, or both, based on your needs.



Front view of Dell PowerConnect 6248



Rear view of Dell PowerConnect 6224/6248 with stacking and 10GE modules shown (Modules optional)



Dell™ PowerConnect™ 6200 Series Switches

Enterprise Support Services Suite

Robust, flexible support for server and storage systems

In today's environment, businesses need smooth and continuous running of their advanced server and storage systems. Maximum uptime is crucial. As an IT professional, you can rely on us for your success. Dell's Enterprise Support Services can help you to:

- eliminate problems before they happen,
- prepare in advance for any elevated IT demands,
- provide the flexibility to match support to the different needs of various end users and applications environments and
- most importantly smartly balancing quality and costs for your organisation.

Choose the Level of Support That's Right for You

Dell offers "best-of-breed" Enterprise Support services at varying levels to help you strike just the right balance between maximum uptime and its associated cost. You can choose a plan that best fits your needs. And thanks to a new, unrivaled foundation we call the Dell ServiceSystem™, you will be backed by innovative best-practice resources.

Platinum Plus Enterprise Support: Dell's most comprehensive level of support. Customised account planning and reporting to proactively improve uptime.

Gold Enterprise Support: Provides rapid resolution of critical issues including escalation management and on-site Emergency Dispatch procedures.

Silver Enterprise Support: Provides convenient 7x24 phone access for hardware and core software troubleshooting with 4-hour 7x24 on-site services following completion of phone-based troubleshooting.

Penang, Malaysia

Dell Asia Pacific Sdn. - Asia Pacific Customer Center
Plot P27 Bayan Lepas Industrial Zone
Phase IV, 11900 Bayan Lepas
Penang, Malaysia

Australia

Dell Australia Pty. Ltd.
Unit 3, 14 Aquatic Drive
Frenchs Forest, NSW 2086
Australia

Hong Kong

Dell Hong Kong Ltd.
1001 Stanhope House
734 - 738 King's Road
Quarry Bay, Hong Kong

India

Dell India Private Limited
Divyashree Greens, Ground Floor
S. No.12/1, 12/2A, 13/1A (Ground Floor)
Varthur-Hobli
Bangalore 560071, India

Malaysia

Dell Asia Pacific Sdn.
Unit 5.01, PJ Tower, Amcorp Trade Centre
18 Jalan Persiaran Barat, off Jalan Timur
46250 Petaling Jaya
Selangor, Malaysia

New Zealand

Dell New Zealand Limited
Unit 1A, Pacific Office Park
4, Pacific Rise, Mount Wellington
Auckland, New Zealand

Singapore

Dell Asia Pte. Ltd.
Co. Reg. No. 198905101W
180 Clemenceau Avenue #06-01
Haw Par Centre, Singapore 239922

Taiwan

Dell B.V. Taiwan Branch
20F, No. 218, Sec. 2, Tung Hwa S. Road
Taipei, Taiwan, R.O.C.

Thailand

Dell Corporation (Thailand) Co. Ltd.
24th Floor Unit 2407, Empire Tower III
195 South Sathorn Road,
Yannawa Sathorn
Bangkok 10120 Thailand

FEATURES

	Dell™ PowerConnect™ 6224	Dell™ PowerConnect™ 6248
Port Attributes	24 10/100/1000BASE-T auto-sensing Gigabit Ethernet ¹ switching ports; 4 SFP combo ports for fiber media support; 10 Gigabit Ethernet ¹ uplink modules (optional); 48Gbps Stacking module (optional); Auto-negotiation for speed, duplex mode and flow control; Auto MDI/MDIX; Port mirroring; Flow-based port mirroring; Broadcast storm control	48 10/100/1000BASE-T auto-sensing Gigabit Ethernet ¹ switching ports; 4 SFP combo ports for fiber media support; 10 Gigabit Ethernet ¹ uplink modules (optional); 48Gbps Stacking module (optional); Auto-negotiation for speed, duplex mode and flow control; Auto MDI/MDIX; Port mirroring; Flow-based port mirroring; Broadcast storm control
Performance	Switch Fabric Capacity 136 Gb/s Forwarding Rate 95 Mpps Up to 8,000 MAC Addresses 256MB of CPU SDRAM 32MB of Flash Memory	Switch Fabric Capacity 232 Gb/s Forwarding Rate 131 Mpps Up to 8,000 MAC Addresses 256MB of CPU SDRAM 32MB of Flash Memory
Availability	Spanning Tree (IEEE 802.1D) and Rapid Spanning Tree (IEEE 802.1w) with Fast Link Support; Multiple spanning trees (IEEE 802.1s); Supports Virtual Redundant Routing Protocol (VRRP); External redundant power support with PowerConnect RPS-600 (sold separately); Cable diagnostics; SFP transceiver diagnostics	
Layer 3 Routing Protocols	Static Routes; Routing Information Protocol (RIP) v1/v2; Open Shortest Path First (OSPF) v1/v2/v3; Classless Inter-Domain Routing (CIDR); Internet Control Message Protocol (ICMP); ICMP Router Discover Protocol (IRDP); Virtual Redundant Routing Protocol (VRRP); Address Resolution Protocol (ARP); Internet Group Management Protocol (IGMP) v2; Distance-Vector Multicast Routing Protocol (DVMRP)	
VLAN	VLAN support for tagging and port-based as per IEEE 802.1Q; Double VLAN tagging (QinQ); Up to 4093 VLANs supported; Dynamic VLAN with GVRP support	
Quality Of Service	Layer 2 Trusted Mode (IEEE 802.1p tagging); Layer 3 Trusted Mode (DSCP); Layer 4 Trusted Mode (TCP/UDP); Advanced Mode using Layer 2/3/4 flow-based Policies, including metering/rate limiting, marking and bandwidth guarantees; up to 1024 ACLs can be used for QoS flow identification via Class-maps; 8 Priority Queues per Port; Adjustable Weighted-Round-Robin (WRR) and Strict Queue Scheduling; Port-based QoS Services Mode; Flow-based QoS Services Mode	
Layer 2 Multicast	Static IP Multicast; Dynamic Multicast Support – 256 Multicast groups supported in IGMP Snooping; IGMP snooping for IP multicast support; IGMP Querier; Protocol Independent Multicast (PIM-DM, PIM-SM)	
Security	IEEE 802.1x based edge authentication; Switch access password protection; User-definable settings for enabling or disabling Web, SSH, Telnet, SSL management access; Port-based MAC Address alert and lock-down; IP Address filtering for management access via Telnet, HTTP, HTTPS/SSL, SSH and SNMP; RADIUS and TACACS+ remote authentication for switch management access; Up to 100 Access Control Lists (ACLs) supported; up to 100 Access Control Entries (ACEs) per ACL list; SSLv3 and SSHv2 encryption for switch management traffic; Management access filtering via Management Access Profiles	
Other Switching Features	Link Aggregation with support for up to 8 aggregated links per switch and up to 8 member ports per aggregated link (IEEE 802.3ad); LACP support (IEEE 802.3ad) Link Layer Discovery Protocol supported (IEEE 802.1AB);	
Management	Web-based management interface; Industry-standard CLI accessible via Telnet or Local Serial Port; SNMPv1, SNMPv2c and SNMPv3 supported; four RMON groups supported (history, statistics, alarms and events); TFTP transfers of firmware and configuration files; Dual firmware images on-board; Multiple configuration file upload/download supported; Statistics for error monitoring and performance optimization including port summary tables; BootP/DHCP IP address management supported; Syslog remote logging capabilities; Temperature sensors for environmental monitoring	
Chassis	Approximate weight (without modules): 5.54 kg Approximate weight (with modules): 5.70 kg 440 x 387 x 43.2 mm (W x D x H); 1U, rack-mounting kit included	Approximate weight (without modules): 6.06kg Approximate weight (with modules): 6.20kg 440 x 387 x 43.2 mm (W x D x H); 1U, rack-mounting kit included

1 This term does not connote an actual operating speed of 1 Gb/sec. For high speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.

2 Technician, replacement part or unit (depending on service contract) will be dispatched if necessary following phone-based troubleshooting. Subject to parts availability, geographical restrictions (on site and/or next business day service not available in some locations) and terms of service contract. Service timing dependent upon time of day call placed to Dell. Defective unit must be returned or paid for. Replacements may be refurbished.

DELL'S NORMAL TERMS AND CONDITIONS APPLY AND ARE AVAILABLE ONLINE OR UPON REQUEST. All efforts will be made to check for errors in typography and photography; however inadvertent errors may occur for which Dell may not be responsible. Dell, the Dell logo and PowerConnect are registered trademarks or trademarks of Dell Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming marks and names or their products. Dell disclaims proprietary interest in the marks and names of others. Copyright 2006 Dell Inc. All rights reserved.



宏權科技股份有限公司

Tel: (03)5553021 · Fax: (03)5584501
新竹縣302竹北市文忠路139號

台北營業處
Tel: (02)27407585 · Fax: (02)27407669
台北市大安區忠孝東路3段48號409室
http://www.nshop.com.tw/

