

# IBM @server xSeries 206



## **Highlights**

- Take advantage of innovative server technology at an entrylevel price
- Leverage flexible configurations and availability on demand for distributed environments and growing business needs
- Enjoy new features that help simplify deployment and improve usability and maintenance

The IBM @server® xSeries® 206 offers value, innovation and usability at affordable prices for small businesses and workgroups. New features help lower IT costs and accommodate growth.

#### Affordable innovation

Help lower total computing cost while optimizing performance:

 New simple-swap Serial ATA drive models can be connected and disconnected easily—usually without a service call.

- New IBM ServeRAID<sup>™</sup> 7e enables you to install and configure RAID 0 or 1 without additional adapters.
- New systems management functions include ASF 2.0, which provides highly secure, remote power on and off control.

### Flexibility for growth

Configure an x206 solution with features that enable future growth. New Intel® Pentium® 4 processors double the speed of previous server generations. Hot-swap SCSI models increase availability as your needs grow. And support for the Remote Supervisor Adapter II helps increase availability with virtual network control as much as 24x7.

#### Easy to deploy, easy to run

Exclusive to the x206, integrated ServeRAID 7e enables RAID 0 and 1 right out of the box. And the improved server design provides ease of access without compromising security.

## Get it now



xSeries 206 at a glance	
Form factor	Tower, rack/4U
Processor	Intel® Pentium® 4 Processor up to 3.0GHz/800MHz front-side bus
<b>Number of processors</b> (std/max)	1/1
Cache (max)	1MB L2
Memory (std/max)	256MB/4GB PC2700 DDR¹ standard (optional PC3200)
Expansion slots	2 PCI-X, 3 PCI
Disk bays (total/hot-swap)	4 non-hot-swap SCSI, 3 hot-swap SCSI, 2 simple-swap SATA (optional 4)
Maximum internal storage	587.2GB <sup>2</sup> SCSI, 320GB SATA, 640GB SATA optional
Network	Integrated 10/100/1000 Ethernet
Power supply (std/max)	340W 1/1
Hot-swap components	Hard disk drives (select models)
RAID support	Integrated IBM ServeRAID 7e (RAID 0,1)
Systems management	IBM Director, Alert Standard Format 2.0, optional IBM Remote Supervisor Adapter II, ServerGuide and optional Remote Deployment Manager
Operating systems supported	Microsoft® Windows® Server 2003 Standard Edition/Enterprise Edition, Windows 2000® Server/Advanced Server, Red Hat® Linux, SUSE LINUX, Novell NetWare, OS 4690
Limited warranty <sup>3</sup>	1-year onsite limited warranty

For more information: World Wide Web		
Canada	ibm.com/ca/eserver/xseries	
Buy Direct		
U.S.	1 888 SHOP IBM	
Canada	1 888 SHOP IBM	
Reseller locator	and general information	
U.S.	1 800 426-4968	
Canada	1 800 426-2255	

Visit ibm.com/pc/safecomputing periodically for the latest information on safe and effective computing.

Warranty Information: For a copy of applicable product warranties, write to: Warranty Information, P.O. Box 12195, RTP, N.C. 27709, Attn: Dept. JDJA/B203. IBM makes no representation or warranty regarding third-party products or services.



© Copyright IBM Corporation 2004

Produced in the USA March 2004 All Rights Reserved

IBM reserves the right to change specifications or other product information without notice. This publication could include technical inaccuracies or typographical errors. References herein to IBM products and services do not imply that IBM intends to make them available in other countries. IBM makes no representations or warranties regarding third-party products or services. IBM PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions; therefore, this disclaimer may not apply to you.

IBM @server systems are assembled in the U.S., Great Britain, Japan, Australia and Brazil and comprise U.S. and non-U.S. components.

IBM, the IBM logo, the e-business logo, @server, ServeRAID and xSeries are trademarks or registered trademarks of IBM Corporation in the United States, other countries or both. For a list of additional IBM trademarks, visit

ibm.com/legal/copytrade.shtml.

Intel and Pentium are registered trademarks of Intel Corporation in the United States, other countries or both.

Microsoft and Windows are registered trademarks of Microsoft Corporation in the United States, other countries or both.

Red Hat, the Red Hat "Shadow Man" logo, and all Red Hat-based trademarks and logos are trademarks or registered trademarks of Red Hat, Inc., in the United States and other countries

Other company, product and service names may be trademarks or service marks of others.

- Memory with Chipkill-enabled technology is available as an option at 512MB DIMMs and higher.
- When referring to storage capacity, GB = 1,000,000,000 bytes. Accessible capacity is less.

